

## Contents

- 1 GNUPG HOW-TO
  - ◆ 1.1 Add User ID
  - ◆ 1.2 KeySigning Procedure
- 2 Extend GPG Expiry

## GNUPG HOW-TO

Run the following from a linux based operating system (e.g. debian) and accept the defaults. Note, it may take some time to generate the random information.

```
gpg --gen-key
```

To see all the keys - yours and your friends etc.:

```
gpg --list-keys
```

Example of above:

```
/home/you/.gnupg/pubring.gpg
-----
pub 1024D/32j38dk2 2001-06-20 you <you@your-address.com>
sub 1024g/289sklj3 2001-06-20 [expires: 2002-11-14]
```

All the public keys you know are stored in the file:  
 ~/.gnupg/pubring.gpg  
 pub = Public Key  
 Public Key ID (UID) = 32j38dk2

To send your key (public) to a person:

```
-o is for a file name (steve)
-a is for an ascii file
gpg --export -o steve -a UID
```

To import a key manually from someone:

```
gpg --import filename
```

Upload Public Key to key server:

```
gpg --send-keys --keyserver wwwkeys.pgp.net UID
```

To edit keys - Typically used for signing keys  
 (cant change name or comment, only password and expiry)

## Gnupg

UID = See example above

```
gpg --edit-key UID
```

To Search for Keys:

(This Will also allow you to download and include the person)

```
gpg --search-key --keyserver wwwkeys.pgp.net stephen burke
```

To Create a gpg fingerprint so you can PRINT out your Key fingerprint:

This allows you to take away to a "Key Signing Party" and sign other keys verifying the person's identity using two forms of id.

```
gpg --fingerprint
```

### Add User ID

Adding in a User ID:

```
gpg --edit-key UID
uid n //Toggles selection of user id with index n. Use 0 to deselect all.
list
```

See the \* beside the Current User id. After current ID is selected type:

```
primary
```

That should be it. Upload keys with command above.

### KeySigning Procedure

See original: <http://www.hants.lug.org.uk/cgi-bin/wiki.pl?LinuxHints/KeySigning>

```
gpg --search-key --keyserver wwwkeys.eu.pgp.net firstname lastname
#Send a signed and encrypted email, asking for a signed reply. When a signed reply is obtained, then
gpg --ask-cert-level --sign-key UID
gpg --send-key UID
```

---

URL's:

[http://webber.dewinter.com/gnupg\\_howto/english/GPGMiniHowto.html](http://webber.dewinter.com/gnupg_howto/english/GPGMiniHowto.html)

<http://www.gnome.org/projects/evolution/doc/x1700.html>

<http://www.nmlug.org/faqs/gen-gpg-key.html>

### Extend GPG Expiry

So my gpg key recently expired and I was wondering why pine was giving out to me saying "no default key available"!

There is a great guide at: <http://www.g-loaded.eu/2010/11/01/change-expiration-date-gpg-key/>

### Some of the main points:

```
gpg --list-keys
gpg --edit-key UID
{type} key 0
expire
//enter new expiry date
{type} key 1
//enter new expiry date
save
gpg --keyserver pgp.mit.edu --send-keys UID
```